


TONE Touch03 - First steps

TONE

1. Remove the grey cover from the housing



2. Connect the blue water house with the TONE TOUCH 03 and your water supply.



Note:
- The TONE 03 needs to be run with filtered water



- The water pressure should be between 0.15 and maximum 0.3 MPa (the flow of the machine is calibrated at the factory with 0.23 MPa). If you

have a standard water pressure which is higher than 0.3 MPa you need to install a pressure regulator.

- The delivered connection adapter from TONE has a 3/8 inch thread



3. Plug the machine into the 230 V socket



4. Build up a connection with a Laptop or tablet to your TONE 03

- Connection by ethernet cable to your laptop or
- Connection by ethernet cable to a lan switch or
- Connection over wifi with the IO-GEAR device

Follow the instructions in the manual / or the specific documents



Touch 03 Manual



TONE-Setup-IO-Gear.pdf

Note: Required operating system on your pc or laptop is **WINDOWS 10**

5. Rinse the machine by pushing the buttons 1 & 2 and the main switch (The two buttons will shine up blue and cold water will rinse through the machine until you switch off the machine) This will help to get rid of the air inside of the brewer system.



6. Calibrate the flow of the machine to its new home. Follow the instructions in the manual.



Touch 03 Manual